



LISTING INFORMATION OF Air Louvers VLFEZ-HRC Vision Frame

SPEC ID: 32787

Air Louvers, Inc. 6285 Randolph St. Commerce, CA 90040

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



WINDSTORM RESISTANT PRODUCTS & COMPONENTS

Model VLFEZ-HRC Hurricane Vision Frame

Door: Single out-swing only, 1-3/4" door, Max 3070

Maximum Size: 24" x 62"

DP Rating (psf): 55

Impact Resistance: 350 ft-lbs, Missle D, Wind Zone 4

Attribute Value

 Criteria
 ASTM E330 (2002)

 Criteria
 ASTM E1886 (2002)

 Criteria
 ASTM E1996 (2003)

 Criteria
 ANSI A250.13 (2003)

Criteria TAS 203
Criteria TAS 201
Criteria TAS 202

 Criteria
 ASTM E1886 (2005)

 Criteria
 ASTM E1996 (2005)

 Criteria
 ANSI A250.13 (2005)

CSI Code 08 11 00 Metal Doors and Frames

DP Rating (psf) 55
Hurricane Impact Load Rating ft-lb 350

Impact Missile Level D
Intertek Services Certification
Listed or Inspected LISTED

Listing Section WINDSTORM - GLAZING SYSTEMS Report Number 3116736-001, 102516327MID-001

Spec ID 32787

^{*} Vision Frame must be installed in a listed windstorm resistant door.

^{*} All doors/walls/components must be rated and listed accordingly.