



TEMPERED GLAZING: TEMP

Safety Glass for Non Fire-Rated Applications Requiring Safety- Rated Glazing.

TEMP SPECIFICATIONS:

Description:	Heat-treated clear safety glass that breaks into small particles.
Thickness:	1/4" (6 mm)
Weight:	2.5 lbs/sq. ft.
Light Transmission:	86% approx.
STC:	31
Fabricated:	USA
Cutting:	Tempered glass cannot be cut after manufacturing.
Size:	Minimum 2" x 2", max. sheet size 83" x 130".
Options at Additional Cost:	<input type="checkbox"/> Obscure frosted glass 1/4" (6 mm). Min size 4" x 4", max size 83" x 130". <input type="checkbox"/> Tinted Glass -Contact Customer Service

LISTINGS & RATINGS:

Impact Safety Rating: CPSC 16CFR 1201 (CAT I & II)

INSTALLATION:

Use glazing compound or glazing tape on both sides of glass, install in an appropriately-listed and labeled vision frame. Certain optical and visual imperfections are inherent in the production process. These characteristics may be evaluated according to the manufacturer's quality standards but do not impair the transparency or affect the performance of the glass, and shall not be considered cause for rejection.

Air Louvers frames for TEMP - VLF, VLFEZ, VSL (Slimline)

LABELING:

Each lite of Tempered Glass will be permanently labeled with the safety rating.

Caution: Tempered glass is not fire-rated, and should not be used where building codes require fire-rated glazing.

STOCK ITEM - THIS ITEM IN STOCK FOR NEXT DAY SHIPMENT IN IN MANY STANDARD SIZES FROM CA AND MN WAREHOUSES

Order Format: TEMP ____ (W) ____ (H)-14 Example: TEMP 2415-14 Note: Order Size is Actual Glass Size

Interpretation of Fire and Building Codes May Vary. Consult with the Local Authority Having Jurisdiction (AHJ) to determine appropriate standards.

<p>© 2021 ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC.</p>	Distributor:	Width: ____ x Height: ____
	Architect:	Quantity:
	Contractor:	
	Project:	Date: Version: 5/25/21

