



0640 Series
Frameless Mirrors
with LED Backlight



0641 Series
Frameless Mirrors
with LED Backlight
and Frosted Border

BACKLIGHTING THAT REFLECTS GREAT DESIGN

Add light to where it's needed the most with ASI's new frameless plate glass mirrors with LED backlight. Combining style with functionality, these mirrors are a perfect fit for any washroom aesthetic from offices to hospitality settings, and are available with frosted borders for extra choice.

FEATURES / BENEFITS:

- 5/32" (4 mm) frameless plate glass with polished edges for user safety
- Glows at 6000 Kelvin
- LED bulbs offer an average savings of \$100 per year* and can have a lifespan of over 50,000 hours.
- Connected through power cord or hardwired
- Can be mounted vertically or horizontally
- Projects 1 3/4" from the wall
- 5 year warranty

**based on 6 hours per day, 7 days per week*

0640 SERIES adds wall accent and soft lighting around the mirror

MODEL NUMBER	OVERALL SIZE (W x H)	LUMENS
0640-2436	24" X 36" (610 X 914 mm)	2352
0640-3036	30" X 36" (762 X 914 mm)	2640
0640-4836	48" X 36" (1219 X 914 mm)	3514
0640-6036	60" X 36" (1524 X 914 mm)	4128

0641 SERIES WITH FROSTED BORDER illuminates the front and sides of the mirror

MODEL NUMBER	OVERALL SIZE (W x H)	LUMENS
0641-2436	24" X 36" (610 X 914 mm)	2352
0641-3036	30" X 36" (762 X 914 mm)	2640
0641-4836	48" X 36" (1219 X 914 mm)	3514
0641-6036	60" X 36" (1524 X 914 mm)	4128



0640 SERIES FRAMELESS MIRRORS WITH LED BACKLIGHT

0641 SERIES FRAMELESS MIRRORS WITH LED BACKLIGHT AND FROSTED BORDER

SPECIFICATION

- Frameless polished edge mirror with integral aluminum mounting frame and frosted glass border LED halo lighting shall be consistent with A glazing (plate glass) and shall be 5/32" [4] thick.
- Hard wired LED lighting system shall be UL listed and shall operate on 100/240 VAC 50/60 Hz.
- Light color shall be the equivalent of 6000 K.
- Unit shall be mountable in horizontal or vertical format without additional brackets or adaptations to mounting provisions.
- Power cord is included for use by owner if appropriate socket is provided on wall (by others) concealed by mounting frame of mirror and is 34" [86] long with 3-prong USA pattern plug and bare wires for connection to hard wiring in LED control box.
- Mirror glass and LED system shall be warranted for manufacturing defects for a period of five (5) years from ship date.
- Keyhole mounting slots are provided for installation in long and short sides of back frame. Mirror is to be hung on pre-installed pan head screws (provided) to be retained by screw heads engaged into the slots.

