ROOF HATCH - Diamond SeriesTM - ROOF HATCH, DIAMOND SERIES 32 X 72 I ALUM, MILL FINISH 79.00 79.00 4 79.00 79.00 79.00 79.00 79.00 79.00 79.00 79.00 79.00

SPECIFICATIONS:

- 1. Curb: 11 gauge mill finish aluminum single wall curb and counterflashing with Diamond Grip.
- 2. Cover: 11 gauge aluminum formed, welded cover with 18 gauge liner, tested to support a live load of 40psf.
- 3. Finish: Mill Finish.
- Gasket: Continuous, weatherproof EPDM sponge rubber adhesive-backed seal.
- 5. Insulation: 1" polyisocyanurate in curb and cover with thermal resistance R-6.
- 6. Spring: Counterbalanced compression springs contained in clear zinc-plated steel cylinders.
- 7. Latch: Clear zinc-plated steel slam latch with inside and outside handles and padlock hasps.
- 8. Hold Open Arm: Clear zinc-plated automatic locking hold open arm with red vinyl grip for one handed door operation.
- 9. Hinge: Heavy duty clear zinc-plated steel pintle hinge.

Notes:

For pitched roofs up to 7:12, mount hinge side parallel to slope. Door opens 75 $^\circ$

Clear Opening: 21" X 66" Weight: 110lbs

MODEL #:

Diamond Series[™] is a trademark of Activar Construction Products Group Inc.

Distributed by


www.AmeraProducts.com

Phone: (800) 608-6568 Fax: (409) 840-5545

info@ameraproducts.com

RHDA-6

3.50 — B — 72.00 LENGTH — SECTION A-A SCALE 1:22



ACTIVAR INC.

CONSTRUCTION PRODUCTS GROUP



Distributor:			Project:	
Contractor:			Approved By:	
Date:	Quantity:		Architect:	
Scale:	Pages:	1 OF 1	Drawing #:	RHDA-6-SUBMITTAL_B