
STAINLESS STEEL MIRROR

- Unbreakable
- Stainless Steel
- No. 8 Architectural Bright Finish





| Bradex ™ Models | | | | |
|------------------------|--------------------|----------------------------|---------------------------------|--------------------------|
| Width (Inches) | Height (Inches) | Overall Dimension (Inches) | Overall Dimension (Millimeters) | Standard Model Number |
| 16" | 24" | 16 x 24 | 406 x 610 | 748-1624 |
| 18" | 24" | 18 x 24 | 457 x 610 | 748-1824 |
| 18" | 36" | 18 x 36 | 457 x 914 | 748-1836 |
| 24" | 36" | 24 x 36 | 610 x 914 | 748-2436 |

APPROVED SUBMITTALS ARE REQUIRED FOR ALL MIRRORS LARGER THAN 24"x 24". In larger sizes, these units are subject to distortion and/or "oil canning" for which Bradley Corporation cannot accept responsibility.

Document No. 8740

MODEL 748

CONSTRUCTION:

- MIRROR fabricated of type 304 (18-8), 20 gauge stainless steel, polished to No. 8 architectural bright finish. Stretcher leveled for uniformity. Very bright — excellent reflectivity, very slight polish grain. 1/4" return conceals backing.
- BACKING of tempered Masonite bonded to mirror with adhesive.
 NOTE: Stainless steel mirrors will differ in optic quality from glass mirrors.

INSTALLATION:

Secure to wall with tamper-resistant mounting screws (included) at holes provided.

NOTE: Provide in-wall backing at mounting screw locations.

GUIDE SPECIFICATION:

Mirror shall be fabricated of type 304 (18-8), 20 gauge stainless steel with No. 8 architectural finish. Unit shall have 1/4" return to conceal 1/4" tempered Masonite backing bonded to mirror with adhesive.

Stainless Steel Mirror shall be Bradley Model 748-____"W x ____"H (specify width and height).

APPROVED SUBMITTALS ARE REQUIRED FOR ALL MIRRORS LARGER THAN 24" X 24".

In larger sizes, these units are subject to distortion and/or "oil canning" for which Bradley Corporation cannot accept responsibility.

